



DASAR PROJECTOR

outdoor floodlight, LED, 3000K, IP68, stainless steel 316, 12-24V, 7W

The surface-mounted DASAR PROJECTOR series lights are fitted with a 7W premium LED and available with a warm-white colour of light. The electrical connection is to a compatible 12V or 24V DC power supply. With IP68 protection class, the luminaire is suitable for outdoor use. The stainless steel DASAR PROJECTOR series includes a further aluminium version, among other things. This luminaire has built-in LED lamps and can be used as a spike luminaire with an earth spike. The lamps in the luminaire cannot be replaced.

TECHNICAL DATA

| | |
|-------------------------|--|
| Item no.: | 233570 |
| Primary nominal voltage | 12-24V mA/V |
| Vertical tilting range | 90 ° |
| Length | 7.2 cm |
| Width | 10.0 cm |
| Height | 10.8 cm |
| Net weight | 1.161 kg |
| Gross weight | 1.244 kg |
| IP Code | IP 68 |
| Safety class | III |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc., Ground, Ground with Acc., Wall, Wall with Acc. |
| Wattage | 7.0 W |
| Lumen | 360 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 40 ° |
| Color | stainless steel |
| CRI | >80 |
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 25000 h |
| BIG WHITE Page | 598 |

Accessories

| | |
|--------|--|
| 233580 | EARTH SPIKE , for DASAR PROJECTOR, stainless steel 316 |
| 233582 | INSTALLATION PLATE , for DASAR PROJECTOR outdoor floodlight, stainless steel 316 |
| 470502 | LED POWER SUPPLY , 12W, 24V |
| 470507 | LED POWER SUPPLY , 12W, 12V |
| 900011 | PLASTIC EARTH SPIKE , black, length 17.5cm |

Notes
