


MEDO 30 EL

LED indoor recessed ceiling light, frameless version, white, 3000/4000K

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



TECHNICAL DATA

| | |
|-------------------------------------|------------------|
| Item no.: | 1001901 |
| Secondary power / secondary voltage | 350 mA/V |
| Height | 9.5 cm |
| Diameter | 28.0 cm |
| Installation diameter | 29.0 cm |
| Installation depth | 13.0 cm |
| Net weight | 1.22 kg |
| Gross weight | 1.679 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 14 W |
| Lumen | 1500 / 1600 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 105 ° |
| Color | white |
| CRI | >80 |
| UGR ≤ | 25 |
| Binning | 3 |
| LXXBXX data | 70/50 |
| Service life | 25000 h |

| | |
|-----------------------------|-------|
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 454 |

Accessories

| | |
|---------|--|
| 1002232 | LED driver , 350mA, 20W, dimmable |
| 1002420 | LED driver MEDO 300 , non-dimmable |
| 1002423 | LED driver MEDO 300 dimmable DALI/1-10V |

Notes
