




MEDO 60 EL

LED indoor recessed ceiling light, frameless version, white, 3000/4000K

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



TECHNICAL DATA

Item no.:	1001903
Secondary power / secondary voltage	10001050 mA/V
Height	12.5 cm
Diameter	60.0 cm
Installation diameter	61.0 cm
Installation depth	16.0 cm
Net weight	5.226 kg
Gross weight	7.23 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	36 W
Lumen	4700 / 5000 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	>80
UGR ≤	25
Binning	3
LXXBXX data	70/50
Service life	25000 h

Maximum ambient temperature	40 °C
BIG WHITE Page	455

Accessories

1001115	LED driver , 1000mA, 40W, dimmable
1002422	LED driver MEDO 600 , non-dimmable
1002425	LED driver MEDO 600 dimmable DALI/1-10V

Notes
