


## DELWA WIDE LED outdoor wall light

3000K, 100°, silver grey, IP44

The DELWA WIDE aluminium wall light is fitted with two powerful flat LEDs with a warm white colour of light. The electrical connection of the aluminium luminaire is made directly to the 230V mains supply using the built-in driver. With protection class IP44, the luminaire is available in several colour versions and is suitable for outdoor use.



### TECHNICAL DATA

|                                     |                           |
|-------------------------------------|---------------------------|
| Item no.:                           | 1000341                   |
| Number of different light outlets   | 1                         |
| Primary nominal voltage             | 100-240V ~50/60Hz mA/V    |
| Secondary power / secondary voltage | 700 mA/V                  |
| Width                               | 14.0 cm                   |
| Height                              | 18.0 cm                   |
| Depth                               | 6.0 cm                    |
| Net weight                          | 0.876 kg                  |
| Gross weight                        | 0.949 kg                  |
| IP Code                             | IP 44                     |
| Safety class                        | I                         |
| Impact resistance class             | IK02                      |
| Impact resistance                   | 0,20000000000000001 Joule |
| Assembly                            | Surface                   |
| Assembly details                    | Wall                      |
| Wattage                             | 10.0 W                    |
| Lumen                               | 910 lm                    |
| Colour temperature                  | 3000 Kelvin               |
| Beam angle                          | 100 °                     |
| Color                               | grey                      |
| CRI                                 | >80                       |
| Binning                             | 6                         |



|                |         |
|----------------|---------|
| LXXBXX data    | 70/50   |
| Service life   | 30000 h |
| BIG WHITE Page | 183     |

**Notes**

---

---

---

---

---