




MEDO 60 EL

LED indoor recessed ceiling light, frame version, white, 3000/4000K

The MEDO FRAME variants round off the recessed lights in the MEDO series. The MEDO FRAME lights blend into any room perfectly, just like the frameless versions. Understated yet still powerful, they provide bright illumination. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



TECHNICAL DATA

Item no.:	1001907
Secondary power / secondary voltage	10001050 mA/V
Height	12.5 cm
Diameter	61.5 cm
Installation diameter	61.0 cm
Installation depth	16.0 cm
Net weight	5.269 kg
Gross weight	7.382 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	36 W
Lumen	4700 / 5000 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	>80
UGR ≤	25
Binning	3
LXXBXX data	70/50
Service life	25000 h

Maximum ambient temperature	40 °C
BIG WHITE Page	456

Accessories

1001115	LED driver , 1000mA, 40W, dimmable
1002422	LED driver MEDO 600 , non-dimmable
1002425	LED driver MEDO 600 dimmable DALI/1-10V

Notes
