




## LED PANEL 620x620

Indoor LED recessed ceiling light white 3000K  
UGR<19

The LED PANEL 620 comes in several different light colours for grid ceilings and provides a modern and space-saving solution for an efficient kind of base lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.



## TECHNICAL DATA

Item no.:	1003073
Secondary power / secondary voltage	1050 mA/V
Length	61.7 cm
Width	61.7 cm
Height	0.9 cm
Installation depth	5.0 cm
Net weight	3.129 kg
Gross weight	3.753 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Wattage	35 W
Lumen	4000 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	>90
UGR ≤	19
Binning	6
LXXBXX data	70/50
Service life	50000 h

## Accessories

1002425	LED driver MEDO 600 dimmable DALI/1-10V
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension
464804	LED DRIVER , 40W, 1050mA, triac dimmable

## Notes

---

---

---

---

---