





VERLUX

recessed fitting, LED, 3000K, matt white, L/B/T
8.5/8.5/4.5 cm, 10W

The light, square recessed VERLUX fitting with a round cut-out is available in various wattages and sizes. The square recessed ceiling light is made of aluminium and comes in a white colour. The rigid Premium LED insert produces homogeneous base lighting thanks to its wide beam angle of 80°. The luminaire comes with a dimmable constant current driver and is ready for connection to the 230 V mains supply.



TECHNICAL DATA

Item no.:	112682
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Length	8.5 cm
Width	8.5 cm
Depth	4.5 cm
Installation diameter	7.5 cm
Installation depth	4.5 cm
Net weight	0.174 kg
Gross weight	0.233 kg
IP Code	IP 20
Safety class	II
Impact resistance class	IK02
Impact resistance	0,20000000000000001 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimming technology	Leading edge
Wattage	12 W
Lumen	880 lm
Colour temperature	3000 Kelvin



Beam angle	80 °
Color	white
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	35000 h
BIG WHITE Page	451

Notes
